



This product is subject to the Arms Export Control Act (22 U.S.C. 7228) and the International Traffic in Arms Regulations (22 C.F.R. Parts 120-130). A prior authorization or license from the U.S. State Department Directorate of Defense Trade Controls is required to export, re-export, re-transfer, or show this document to any foreign person whether in the United States or abroad.

MOE SL-S STOCK




MAG653 MOE SL-S STOCK Mil-Spec

♠ WADA

WARNING: BEFORE STARTING, MAKE SURE THE WEAPON IS UNLOADED, THE CHAMBER IS EMPTY, AND THE SAFETY ENGAGED.

INSTALLATION INSTRUCTIONS


SL-S STOCK OPERATION



STEP 1: REMOVE EXISTING STOCK


Remove existing stock per armory guidelines.

Refer to US Army TM 9-1005-319-23&P for assistance.



REMOVE BATTERY TUBE PLUG


To remove the rubber *Battery Tube Plug*, pull rear of the plug away from the *Stock Body* and then pull the plug out of the tube.



STEP 2: INSTALL STOCK

DO NOT FORCE PARTS TOGETHER! Align the Stock Body with the carbine receiver extension and gently slide together until the stock stops (approx 2-1/8"). Depress Release Latch with first hand. Insert a 3/32" hex wrench into Lock Plate and pull down until Lock Pin can be inserted past the end of the carbine receiver extension. Push stock forward to mount.


NOTE: If stock does not easily slide over receiver extension, refer to fit guide in box.



REINSTALL BATTERY TUBE PLUG

To reinstall *Battery Tube Plug*, push front of plug into tube, then firmly push rear of plug into tube reliefs until fully captured.

NOTE: Battery Tubes will accommodate CR123 and AA batteries.



STEP 3: VERIFY INSTALL

Perform final inspection including function test per US Army TM 9-1005-319-23&P Unit and Direct Support Maintenance Manual to verify correct installation. If you experience any issues during installation, please contact us at www.magpul.com. Always test fire your weapon before using it in an operational environment.