





This document is subject to the Arms Export Control Act (22 U.S.C. 7228) and the International Traffic in Arms Regulations (22 C.F.R. Parts 120-130). A prior authorization or license from the U.S. State Department Directorate of Defense Trade Controls is required to export, re-export, re-transfer, or show this document to any foreign person whether in the United States or abroad.

MOE[®] SL[™] STOCK




INSTALLATION INSTRUCTIONS

⚠ WARNING: BEFORE STARTING, MAKE SURE THE WEAPON IS UNLOADED, THE CHAMBER IS EMPTY, AND THE SAFETY ENGAGED.



STEP 1: REMOVE EXISTING STOCK


Remove existing stock per armory guidelines.
Refer to **US Army TM 9-1005-319-23&P** for assistance.



STEP 2: INSTALL STOCK

DO NOT FORCE PARTS TOGETHER! Align the *Stock Body* with the *carbine receiver extension* and gently slide together until the stock stops (approx 2-1/8"). Depress *Release Latch* with first hand (A). With other hand, grasp both ends of *Release Pin* and pull down firmly (B). Push stock forward to mount.

NOTE: If stock does not easily slide over receiver extension, refer to fit guide in box.



STEP 3: VERIFY INSTALL

Perform final inspection including function test per **US Army TM 9-1005-319-23&P Unit and Direct Support Maintenance Manual** to verify correct installation. If you experience any issues during installation, please refer to the "Related Info" tab, located on the product page at www.magpul.com. Always test fire your weapon before using it in an operational environment.